



DEXTER
LAUNDRY

On-Premise Double Load T-300 Washer

(Model WCVD18HCS-10,
120 Volt)

(Model WCVD18HCS-12,
208-240 Volt)



On-Premise Double Load T-300 Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance, and programming capabilities.

Durable Design

- **Save water** with "sump free" design
- **304 Stainless Steel cylinder, outer tub, top, front, and side panels** keep Dexter washers looking good
- **Heavy-duty Sur-Coat Frame** is built like a battleship to last a lifetime
- **Over-sized bearings and seals** run smooth and add to machine life

VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity** demand by eliminating spike usage

100 G-Force Extraction

- **Save drying energy** with 100 G-Force washers that remove more water
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** cycles, water temperatures, supply inputs and more

Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easily connected** to automatic supply injection systems.
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



Door Locks when machine starts, and remains locked until cycle is completed. If power is interrupted, there will be a 2 to 3 minute delay before the door can be opened.

T-300 OPL Washer Specifications

CAPACITY

Load Size	Double Load	
Dry Weight Capacity	18 lbs	8.11 kg
Cylinder Diameter	21"	53.3 cm
Cylinder Depth	13.5"	34.3 cm
Cylinder Volume	2.7 cu ft	76.6 dm ³

DIMENSIONS

Cabinet Height	43.88"	111.44 cm
Cabinet Width	26"	66.04 cm
Overall Depth	24.81"	63.02 cm
Floor to Door Bottom	15"	38.1 cm
Door Opening	12.25"	31.1 cm

WASHING/EXTRACTION

High Extract Speed	100 G-Force	579 RPM
Intermediate Extract Speed	60 G-Force	449 RPM
Washing Speed	55 RPM	
Motor Size	1 HP	.75 Kw

ELECTRICAL (120 Volt)

Electrical Phase	Single
Electrical Voltage (60 Hz)	120 volts
Electrical Running (Amps)	13
Circuit Protection (Amps)	20 amp
Electrical Wire Size	Cord Provided
Electrical Service (Single Phase)	Cord Provided
Electrical Service (Three Phase)	NA

ELECTRICAL (208-240 Volt)

Electrical Phase	Single or Three
Electrical Voltage (60 Hz)	208-240 volts
Electrical Running (Amps)	4
Circuit Protection (Amps)	15 amp
Electrical Wire Size	14 gauge
Electrical Service (Single Phase)	2 wire + ground
Electrical Service (Three Phase)	3 wire + ground

WATER

Water Inlet Size	3/4"	19mm
Water Flow Rate (per minute)	9 gal	34.06 L
Water Pressure (min/max)	30-120 psi	207-827 Kpa
Drain Diameter (O.D.)	2.25"	5.7 cm
Floor to Center of Drain	6"	15.24 cm

INSTALLATION

Net Weight	326 lbs	146.8 kg
Clearance Between Machines	1/2" (min)	1.27 cm
Clearance Behind Machines	24" (min)	60.96 cm
Concrete Thickness	6" (min)	15.24 cm



DEXTER
LAUNDRY

Dexter Laundry, Inc.
2211 W. Grimes, Fairfield, Iowa 52556
www.dexterlaundry.com
1-800-524-2954

© 2007, Dexter Laundry Inc.
Dexter reserves the right to change features or specifications without notice.



Convenient Soap Dispenser



Easy Programming



Large Loading Door



Heavy Duty Construction