



DEXTER
LAUNDRY

Commercial Maxi Load T-600 Washer

(Model WCAD40KCS-12)



Maxi Load T-600 Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance and programming capabilities.

Commercial Design

- **Save water** with “sump free” design
- **304 Stainless Steel** keeps Dexter washers looking good
- **Heavy-duty** Sur-Coat Frame is built to last like a battleship
- **Over-sized bearings and seals** run smooth and add to machine life

VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity** demand by eliminating spike usage

100 G-Force Extraction

- **Save drying energy** with 100 G-Force extraction
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** pricing, cycles, water temps, supply inputs and more
- **Offer plus cycle**, time of day, and tiered pricing
- **Network capable** with included communication port

Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



Commercial T-600 Specifications

CAPACITY

		Maxi Load
Load Size		
Dry Weight Capacity	40 - 45 lbs.	18.2-20.4 kg
Cylinder Diameter	25"	63.5 cm
Cylinder Depth	21.13"	53.7 cm
Cylinder Volume	6 cu ft	170.1 dm ³

DIMENSIONS

Cabinet Height	49.75"	126.37 cm
Cabinet Width	29.88"	75.88 cm
Overall Depth	36"	91.44 cm
Floor to Door Bottom	16"	40.64 cm
Door Opening	15.25"	38.74 cm

WASHING/EXTRACTION

High Extract Speed	100 G-Force	532 RPM
Intermediate Extract Speed	60 G-Force	412 RPM
Washing Speed	50 RPM	
Motor Size	2 HP	1.5 Kw

ELECTRICAL

Electrical Phase	Single or Three
Electrical Voltage (60 Hz)	208-240 volts
Electrical Running (Amps)	6.2
Circuit Protection (Amps)	20 amp
Electrical Wire Size	12 gauge
Electrical Service (Single Phase)	2 wire + ground
Electrical Service (Three Phase)	3 wire + ground

WATER

Average Water Usage*	43 gal	162.76 L
Maximum Hot Water Usage*	18 gal	68.13 L
Water Inlet Size	3/4"	19mm
Water Flow Rate (per minute)	9 gal	34.06 L
Water Pressure (min/max)	30-120 psi	207-827 Kpa
Drain Diameter (O.D.)	3"	7.62 cm
Floor to Center of Drain	5"	12.7 cm

INSTALLATION

Net Weight	631 lbs	286.2 kg
Clearance Between Machines	1/2" (min)	1.27 cm
Clearance Behind Machines	24" (min)	60.96 cm
Concrete Thickness	6" (min)	15.24 cm



DEXTER
LAUNDRY

Dexter Laundry, Inc.

2211 W. Grimes, Fairfield, Iowa 52556

www.dexterlaundry.com

1-800-524-2954

© 2008, Dexter Laundry, Inc.

Dexter reserves the right to change features or specifications without notice.



Available with coin drop, programmable electronic drop or Easy Card™.



Easy Programming



Large Loading Door



Emergency Stop Button