

Express Stack Dryer Specifications

Model - Model No.

	T30x2 - DDAD30	T50x2 - DDAD50
Cabinet Height - in (mm)	76.25" (1937)	79.625" (2023)
Cabinet Width - in (mm)	31.5" (800)	34.5" (877)
Overall Depth - in (mm)	50.0" (1270)	53" (1346)
Floor to Door Bottom - in (mm)	7.31" (186)	7.27" (185)
Door Opening - in (mm)	22.69" (576)	25.69" (653)
Dry Wt. Capacity - lbs (kg)	30 x 2 (13.6 x 2)	50 x 2 (22.7 x 2)
Cylinder Diameter - in (mm)	30" (762)	32.5" (826)
Cylinder Depth - in (mm)	27.5" (699)	33" (769)
Cylinder Volume - cu.ft. (liters)	11.25 (318)	15.84 (448)
Lint Screen Area - sq.in. (sq.cm)	442 (2852)	536 (3458)
Gas Input/Hour (kW) (per pocket)	90,000BTU (26.4)	120,000BTU (35.2)
Gas Supply Connection - in (mm)	.5" (12.7)	.5" (12.7)
Natural Gas Supply (Water Column)	4-10"	4-10"
L.P. Supply (Water Column)	11.5-14"	11.5-14"
Exhaust Size - in (mm)	8" (203)	8" (203)
Make-up Air	1.5 sq.ft. (1394sq.cm)	1.5 sq.ft. (1394sq.cm)
Motor Size	1/2 H.P. (.373kW)	3/4 H.P. (.560kW)

Electrical Specifications - 120/60/1

	T30x2 - DDAD30	T50x2 - DDAD50
Voltage/Hz/Phase	120V/60Hz/1Phase	120V/60Hz/1Phase
Running Amps	19.6	24.0
Circuit Protection Amps	30	30
Wire Size	10 gauge	10 gauge
Electrical Service	2 wire + ground	2 wire + ground

Electrical Specifications - 220-240/60/1

	T30x2 - DDAD30	T50x2 - DDAD50
Voltage/Hz/Phase	220-240V/60Hz/1Phase	220-240V/60Hz/1Phase
Running Amps	10.0	12.0
Circuit Protection	15	20
Wire Size	12 gauge	12 gauge
Electrical Service	3 wire + ground	3 wire + ground

Electrical Specifications - 220-240/50/1

	T30x2 - DDAD30	T50x2 - DDAD50
Voltage/Hz/Phase	220-240V/50Hz/1Phase	220-240V/50Hz/1Phase
Running Amps	10.0	12.0
Circuit Protection	15	20
Wire Size	12 gauge	12 gauge
Electrical Service	3 wire + ground	3 wire + ground

Shipping Weight - lbs (kg)	773 (351)	950 (431)
Net Weight - lbs (kg)	685 (311)	850 (386)
Clearance Behind Machines (Min.)	18" (457)	18" (457)



Available with coin drop, programmable electronic drop or Easy Card™.



Easy Programming



Large Loading Doors



Efficient Burner Design



DEXTER
LAUNDRY

Dexter Laundry, Inc.

2211 W. Grimes, Fairfield, Iowa 52556

www.dexterlaundry.com

1-800-524-2954



DEXTER
LAUNDRY

Dexter
EXPRESS
Stack Dryers



(Model T30x2 - DDAD30)



(Model T50x2 - DDAD50)

Dexter *EXPRESS* Stack Dryers

Dexter's new EXPRESS 50lb model joins our EXPRESS 30lb model and gives coin laundry owners capacity and performance that no other stack dryer can match.

With a long-standing reputation for having the best performing, and most reliable stack dryer on the market, Dexter's newest model takes the industry to a whole new level of capacity, while still delivering the drying performance and energy efficiency that Dexter is famous for.

Both sizes of Dexter EXPRESS stack dryers are perfectly tuned to maximize drying performance and energy efficiency. By balancing heat input, tumble speed, air recirculation, and airflow through our fully-perforated, large-diameter cylinders, Dexter dryers deliver maximum energy efficiency and superior drying speed. And the added flexibility of multiple sizes allows stores to not only increase their drying capacity, but also to better match washer sizes with dryer sizes – a real convenience for customers.

In today's competitive market, if you're looking for a way to grow your business without adding additional floor space to your laundry, Dexter stack dryers are for you. Your local Dexter authorized distributor can show you how replacing your existing dryers with new Dexter stacks will improve your profits and return on investment.

